



## AHR EXPO 2020 Product Information

### **Laars OmniTherm® Near Condensing Boilers and Volume Water Heaters – NEW!**

OmniTherm® boilers and volume water heaters are available in six sizes from 1250 to 3000 MBH, with stainless steel heat exchangers and Laars Linc® intuitive controls. Advanced electronic air-to-fuel ratio control produces up to 7:1 turndown and thermal efficiencies as high as 87%. Install in Category I, II, III or IV vent systems.

---

### **Laars OmniTherm® Near Condensing Boilers and Volume Water Heaters – NEW!**

OmniTherm® near condensing boilers and volume water heaters are available in six sizes from 1250 to 3000 MBH, offers up to 7:1 turndown and thermal efficiencies as high as 87%. Each OmniTherm is built with a long-life stainless steel heat exchanger and the latest in electronic air-to-fuel ratio control.

OmniTherm units can be installed in Category I, II, III or IV vent systems for new or replacement applications and in low return water temperature applications regardless of vent category.

Included Laars Linc® control system with color touchscreen is easy to use, displays key performance measures, and has a quick start feature.



### **IMPORTANT**

If you are interested in releasing any of this product information prior to the AHR EXPO 2020, please contact:

**Chuck O'Donnell**  
**Director of Marketing**  
**Laars Heating Systems**  
**[codonnell@laars.com](mailto:codonnell@laars.com)**